



Qingdao Bonway Industrial Co., Ltd.
Add: Jianguo Building, No. 519 Middle
Changjiang Road, West Coast, Qingdao,
Shandong, China
Tel/WhatsApp: +86 17685832845

SD838

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

Good driving performance Good chunking resistance Good loading performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12R22.5	18PR	16.5	9.00	3550/3250	152/149	K	930

SA866

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

Ultra-high mileage Good irregular wear resistance Excellent durability

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12R22.5	18PR	17.0	9.00	3550/3250	152/149	L	930

SA859

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

Ultra-high mileage Good irregular wear resistance Excellent durability

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12R22.5	18PR	17.0	9.00	3550/3250	152/149	L	930

SA868

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Good durability and loading performance Good traction performance Good adaptability of road surface

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11.0R20	18PR	16.5	8.0	3050/2250	152/149	K	930
12.0R20	20PR	17.0	8.5	4000/3650	156/153	K	930

SA878

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

Widened tread design Excellent durability High strength steel belt structure

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12R22.5	18PR	17.5	9.00	3550/3250	152/149	L	930

ST903

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

High mileage Reinforced skeleton material design Optimized tire grounding design prevents irregular wear

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
245/70R17.5	18PR	16.0	7.50	2120/2000	134/132	L	900
245/70R19.5	14PR	14.0	7.50	2180/2040	135/133	L	830

SA898

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Excellent grip Excellent durability and loading performance Good heat dissipation on shoulder

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12.0R20	20PR	16.5	8.5	4000/3650	156/153	K	900

ST917

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

Low heat formula design Optimized groove bottom design Strengthen bead design

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
295/80R22.5	18PR	16.5	9.00	3550/3250	152/149	L	900

SD939

SUITABLE FOR MID-SHORT DISTANCE NATIONAL HIGHWAY TRANSPORTATION

Strong driving and braking performance Good heat dissipation performance on shoulder Excellent grip performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
295/80R22.5	18PR	18.0	9.00	3550/3250	152/149	L	900

ST970

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

Excellent wear resistance Low fuel consumption Low heat of tread formula

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
385/65R22.5	20PR	16.7	11.75	4000	160	K	900
385/65R22.5	24PR	16.7	11.75	5000	164	K	900
385/65R22.5	20PR	16.5	12.25	4000	160	K	900

ON&OFF

SD358

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF ROUGH ROADS

Low heat and anti-wear formula design Excellent driving/braking performance Excellent durability

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11R22.5	14PR	22.0	8.25	3000/2775	146/143	L	830

SD369

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Good driving performance Anti-clamping stone design Good durability and loading performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12.0R20	20PR	19.0	8.5	4000/3650	156/153	K	900

SD359

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Good tear resistance performance Good driving/braking performance Good loading performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12.0R20	20PR	18.5	8.5	4000/3650	156/153	K	900

SD767

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF MINING AREA AND MIXED ROADS

Excellent grip and driving performance Excellent durability Tear resistance pattern groove

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12R22.5	18PR	20.5	9.00	3550/3250	152/149	D	930

SD305

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF ROUGH ROADS

Good driving/braking performance Good durability Low heat formula

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
425/65R22.5	22PR	16.0	12.25	5300	166	K	900

SD307

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Good durability and loading performance Good driving and grip performance Good anti-clamping stone performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
9.0R20	16PR	18.5	7.0	2800/2450	144/142	K	900
10.0R20	18PR	19.0	7.5	3250/3000	149/146	K	930

SD306

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Low heat generation Excellent grip/anti-skid performance Strengthened carcass and bead

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
7.50R14L7	14PR	15.5	6.00	1000/730	122/118	K	770
8.25R14L7	18PR	15.0	6.50H	2000/1800	132/128	K	870
9.00R20	14PR	18.5	7.0	2800/2650	144/142	K	900
12.0R20	18PR	19.5	7.5	3250/3000	149/146	K	930

SD312

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Excellent driving/braking performance Good heat dissipation on shoulder Strong carcass and bead performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11.0R20	18PR	20.0	8.0	3550/3250	152/149	K	930

SD318

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF ROUGH ROADS

Excellent grip driving performance Excellent puncture resistance performance Deepened pattern groove design

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
295/80R22.5	18PR	24.0	9.00	3550/3250	152/149	K	900

SD837

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF MINING AREA AND MIXED ROADS

Tear resistance pattern groove Excellent grip and driving performance Crown explosion-proof performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12R22.5	18PR	20.5	9.00	3550/3250	152/149	K	930

SD308

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF ROUGH ROADS

Good driving/braking performance Good durability Low heat formula

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
315/80R22.5	20PR	20.5	9.00	4120/3750	193/154	K	900

SD319

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Good loading performance Good driving performance Good anti-clamping stone performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
13R22.5	20PR	21.0	9.75	4000/3650	156/153	K	930
11.0R20	18PR	20.0	8.0	3550/3250	152/149	K	930
12.0R20	20PR	21.0	8.5	4000/3650	156/153	K	900

SD357

SUITABLE FOR MID-SHORT DISTANCE TRANSPORTATION OF PAVED ROAD AND MIXED ROAD

Excellent grip and driving performance Good tear resistance performance Good braking performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11R22.5	16PR	23.0	8.25	3000/2775	146/143	G	830
11R24.5	16PR	21.0	8.25	3250/3000	149/146	G	830

SD717

SUITABLE FOR MINING AREA AND ROUGH ROADS TRANSPORTATION

Excellent puncture resistance cut and chip resistance Excellent driving and braking performance Excellent loading performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11.0R20	18PR	24.0	8.0	3550/3250	152/149	D	930
12.0R20	20PR	25.0	8.5	4000/3650	156/153	D	930

SD737

SUITABLE FOR MINING AREA AND ROUGH ROADS TRANSPORTATION

Excellent puncture performance Strong driving force Excellent loading performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
7.50R14L7	14PR	16.5	6.00	1050/1020	125/121	D	870
8.25R14L7	18PR	20.0	6.50H	2000/1800	132/128	D	870
9.00R20	14PR	22.5	7.0	2800/2650	144/142	D	900
10.0R20	16PR	23.0	7.5	3250/3000	149/146	D	930
12.0R20	20PR	24.0	8.5	4000/3650	156/153	D	900

SD757

SUITABLE FOR MINING AREA AND ROUGH ROADS TRANSPORTATION

Excellent puncture resistance Strong driving force Excellent loading performance

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
12.0R20	20PR	23.0	8.5	4000/3650	156/153	G	930
13R22.5	20PR	23.0	9.75	4000/3650	156/153	G	930

WINTER

SD378S

SUITABLE FOR SNOW-COVERED ROAD TRANSPORTATION

3D side design Excellent skid resistance Excellent traction braking Special snow tread formula design

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11R22.5	16PR	21.0	8.25	3000/2775	146/143	K	830
11R24.5	16PR	21.0	8.25	3250/3000	149/146	K	830
295/70R22.5	16PR	22.0	9.00	3000/2775	146/143	K	830

SDA01

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

3D siping design improves grip Excellent handling performance Excellent durability

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11R22.5	16PR	22.0	8.25	3000/2775	146/143	K	830
11R24.5	16PR	22.0	8.25	3250/3000	149/146	K	830

SDA02

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

3D siping design improves grip Excellent handling performance Excellent durability

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11R24.5	16PR	22.5	8.25	3250/3000	149/146	K	830

SDA05

SUITABLE FOR MID-LONG DISTANCE NATIONAL HIGHWAY TRANSPORTATION

3D siping design improves grip Excellent handling performance Excellent durability

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
225/70R19.5	16PR	14.0	6.75	1800/1700	130/124	H	740
225/70R19.5	16PR	14.0	6.75	1950/1800	130/128	L	830
225/70R19.5	18PR	14.0	6.75	2000/1700	132/130	K	900

SD377S

SUITABLE FOR SNOW-COVERED ROAD TRANSPORTATION

3D side design Excellent skid resistance Excellent traction/braking Special snow tread formula design

SIZE	PLY RATING	TREAD DEPTH (mm)	STANDARD RIM	LOAD SINGLE / DUAL	LOAD INDEX	SPEED RATE	AIR PRESSURE (kPa)
11R22.5	16PR	21.0	8.25	3000/2775	146/143	K	830
11R24.5	16PR	21.0	8.25	3250/3000	149/146	K	830
295/70R22.5	16PR	22.0	9.00	3000/2775	146/143	K	830



